

**CAÑOS Y TUBOS DE ACEROS INOXIDABLES AUSTENITICOS**

**TUBOS DE ACERO AUSTENITICO C/SIN COSTURA NORMA ASTM A 249**

Peso por metro de long. (Kg./m.)

DIAM. EXT. PULGADAS	DIAM. EXT. MILIMETROS	ESPESOR EN MILIMETROS								
		0,8	0,9	1	1,25	1,5	2	3	4	5
1/2	12,70	0,249	0,278	0,306	0,375	0,440				
5/8	15,87	0,312	0,334	0,386	0,474	0,559				
3/4	19,05	0,376	0,405	0,465	0,553	0,679	0,881			
7/8	22,20	0,440	0,492	0,545	0,673	0,798	1,040			
1	25,40	0,504	0,564	0,625	0,773	0,919	1,200			
1-1/8	28,58	0,568	0,636	0,705	0,873	1,038	1,359	1,954		
1-1/4	31,75	0,631	0,708	0,784	0,973	1,158	1,518	2,263		
1-1/2	38,10		0,852	0,944	1,172	1,397	1,837	2,681		
1-3/4	44,50		0,995	1,103	1,371	1,636	2,157	3,160		
2	50,80			1,263	1,571	1,875	2,476	3,645		
2-1/2	63,50				1,970	2,354	3,114	4,615		
3	76,20					2,832	3,752	5,585	7,302	
4	101,50					3,800	5,028	7,525	9,855	12,193
5	127,00						6,304	9,380	12,407	15,383
6	152,40						7,580	11,295	14,959	18,573
8	203,20						10,130	15,123	20,063	24,954
10	254,00						12,684	18,951	25,168	31,334
12	304,00							22,780	30,780	37,715

**TABLA 3/2**